



(11) **EP 0 947 172 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
**06.10.1999 Bulletin 1999/40**

(51) Int Cl.<sup>6</sup>: **A61B 17/36**

(21) Application number: **99200974.6**

(22) Date of filing: **29.03.1999**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU**  
**MC NL PT SE**  
 Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventor: **Schatzberger, Shaiké**  
**34987 Halfa (IL)**

(74) Representative:  
**Iemenschot, Johannes Andreas, Ir.**  
**van Exter Polak & Charlouis B.V.,**  
**P.O. Box 3241**  
**2280 GE Rijswijk (NL)**

(30) Priority: **31.03.1998 US 52165**


(71) Applicant: **Galil Medical Ltd**  
**Yokneam 20692 (IL)**

(54) **High resolution cryosurgical method and apparatus**

(57) A high resolution cryosurgical method and device for treating a patient's prostate are provided. The method includes the steps of (a) introducing a plurality of cryosurgical probes (53) to the prostate, the probes (53) having a substantially small diameter, the probes (53) being distributed across the prostate, so as to form an outer arrangement of probes adjacent the periphery of the prostate and an inner arrangement of probes adjacent the prostatic urethra; (b) producing an ice-ball at the end of each of said cryosurgical probes (53), so as to locally freeze a tissue segment of the prostate. The apparatus includes (a) a plurality of cryosurgical probes (53) of small diameter, the probes being for insertion into

the patient's organ, the probes (53) being for producing ice-balls for locally freezing selected portions of the organ; (b) a guiding element (110) including a net of apertures (120) for inserting the cryosurgical probes (53) therethrough; and (c) an imaging device (130) for providing a set of images, the images being for providing information on specific planes located at specific depths within the organ, each of said images including a net of marks (117) being correlated to the net of apertures (120) of the guiding element (110), wherein the marks (117) represent the locations of ice-balls which may be formed by the cryosurgical probes (53) when introduced through said apertures (120) of the guiding element (110) to said distinct depths within the organ.

FIG. 6a



## Description

### FIELD AND BACKGROUND OF THE INVENTION

[0001] The present invention relates to high resolution cryosurgical method and apparatus which enable to effectively and accurately freeze and thereby destroy a predetermined portion of a tissue while minimizing damage to adjacent tissues and organs.

[0002] Cryosurgical procedures involve deep tissue freezing which results in tissue destruction due to rupture of cells and/or cell organelles within the tissue. Deep tissue freezing is effected by insertion of a tip of a cryosurgical device into the tissue, either endoscopically or laparoscopically, and a formation of, what is known in the art as, an ice-ball around the tip.

[0003] In order to effectively destroy a tissue by such an ice-ball, the diameter of the ball should be substantially larger than the region of the tissue to be treated, which constraint derives from the specific profile of temperature distribution across the ice-ball.

[0004] Specifically, the temperature required for effectively destroying a tissue is about  $-40^{\circ}\text{C}$  or cooler. However, the temperature at the surface of the ice-ball is  $0^{\circ}\text{C}$ . The temperature declines exponentially towards the center of the ball such that an isothermal surface of about  $-40^{\circ}\text{C}$  is typically located within the ice-ball substantially at the half way between the center of the ball and its surface.

[0005] Thus, in order to effectively destroy a tissue there is a need to locate the isothermal surface of  $-40^{\circ}\text{C}$  at the periphery of the treated tissue, thereby exposing adjacent, usually healthy, tissues to the external portions of the ice-ball. The application of temperatures of between about  $-40^{\circ}\text{C}$  and  $0^{\circ}\text{C}$  to such healthy tissues usually causes substantial damage thereto, which damage may result in temporary or permanent impairment of functional organs.

[0006] In addition, should the adjacent tissues be present at opposite borders with respect to the freeze treated tissue, such as in the case of prostate freeze treatments, as further detailed below, and since the growth of the ice-ball is in substantially similar rate in all directions toward its periphery, if the tip of the cryosurgical device is not precisely centered, the ice-ball reaches one of the borders before it reaches the other border, and decision making of whether to continue the process of freezing, risking a damage to close healthy tissues, or to halt the process of freezing, risking a non-complete destruction of the treated tissue, must be made.

[0007] Although the present invention is applicable to any cryosurgical treatment, discussion is hereinafter focused on a cryosurgical treatment of a patient's prostate.

[0008] Thus, when treating a tumor located at a patient's prostate, there is a trade-off between two options: (a) effectively destroying the prostatic tissue extending between the prostatic urethra and the periphery of the

prostate and causing unavoidable damage to the patient's urethra or organs adjacent the prostate such as the rectum and nerves; (b) avoiding the damaging of the prostatic urethra and adjacent organs, but exposing the patient to the risk of malignancy due to ineffective destruction of the prostate tumor.

[0009] Currently, cryosurgery procedures for treating the prostate include the introduction of 5-7 probes into the prostate, the probes being typically arranged around the prostatic urethra such that a single probe is located, preferably centered, between the prostatic urethra and the periphery of the prostate. The dimensions of such a single probe are usually adapted for effectively treating the prostatic tissue segment extending from the urethra to the periphery of the prostate, e.g., a tip of 3 millimeters in diameter, generating an ice-ball of 3-4 centimeters in diameter, depending on the size of the prostate. Since a single ice-ball is used for freezing such a prostatic tissue segment, the volume of adjacent tissues exposed to damage is substantially greater than the volume of the treated tissue. - For example, if the area of the ice-ball in cross section is  $\pi R^2$ , and an effective treatment of at least  $-40^{\circ}\text{C}$  is provided to an area of  $\pi(R/2)^2$  (in cross section), then the area of adjacent tissues (in cross section) exposed to between about  $-40^{\circ}\text{C}$  and about  $0^{\circ}\text{C}$  is  $\pi R^2 - 0.25(\pi R^2) = 0.75(\pi R^2)$ , which is three times the area of the tissue effectively treated by the ice-ball.

[0010] The current strategy used for avoiding excessive damage to adjacent tissues is to use such a single probe of a smaller diameter producing an ice-ball of smaller size, thereby exposing the patient to the danger of malignancy.

[0011] Thus, the prior art methods and devices fail to provide effective resolution of treatment along the planes perpendicular to the axis of penetration of the cryosurgical probe into the patient's organ.

[0012] Furthermore, since anatomical organs such as the prostate usually feature an asymmetric three dimensional shape, the introduction of a cryosurgical probe along a specific path of penetration within the organ may provide effective treatment to specific regions located at specific depths of penetration but at the same time may severely damage other portions of the organ located at other depths of penetration.

[0013] There is thus a widely recognized need for, and it would be highly advantageous to have, cryosurgical method and device which provide high resolution of treatment along the axis of penetration of the cryosurgical probe into the patient's organ as well as along the planes perpendicular to the axis of penetration.

[0014] Specifically, there is a widely recognized need for, and it would be highly advantageous to have, high resolution cryosurgical method and device which enable to effectively destroy selective portions of a patient's tissue while minimizing damage to adjacent tissues and organs.

[0015] Furthermore, there is a widely recognized

need for such method and device which enable to selectively treat various portions of the tissue located at different depths of the organ, thereby effectively freezing selected portions of the tissue while avoiding the damaging of other tissues and organs located at other depth along the axis of penetration.

[0016] It would be further advantageous to have such cryosurgical method and device which three dimensionally map an organ of a patient so as to form a three dimensional grid thereof, and which apply a multi-probe system introduced into the organ according to the grid so as to enable systematic high-resolution three dimensional cryosurgical treatment of the organ and selectively destroy the treated tissue with minimal damage to surrounding, healthy, tissues.

### SUMMARY OF THE INVENTION

[0017] According to the present invention there is provided a high resolution cryosurgical method for treating a patient's prostate, comprising the steps of (a) introducing a plurality of cryosurgical probes to the prostate, the probes having a substantially small diameter, the probes being distributed across the prostate so as to form at least an outer arrangement of probes adjacent to the periphery of the prostate and an inner arrangement of probes adjacent to the prostatic urethra; (b) producing an ice-ball at the end of each of the cryosurgical probes so as to locally freeze a tissue segment of the prostate.

[0018] Some or all of the probes may be distributed along the inner and outer arrangements so as to form pairs of probes, each pair including an inner probe adjacent to the prostatic urethra and an outer probe adjacent to the periphery of the prostate. However, since the periphery of the prostate is larger than its core, the number of probes in the outer arrangement typically exceeds the number of probes in the inner arrangement.

[0019] Preferably, the diameter of the cryosurgical probes is between about 0.2 and 1.4 millimeters, preferably between about 1 and 1.4 millimeters, typically about 1.2 millimeters, generating ice-balls of about 2 centimeters in diameter or less. As used herein the term "about" refers to  $\pm 20\%$ .

[0020] The above arrangement of probes ensures the formation of at least two adjacent (e.g., close within less than about 1 millimeter, tangent or overlapping) ice-balls in each prostate section, one being closer to the periphery of the prostate and the other being closer to the urethra, each of the ice-balls featuring a diameter of 2 centimeters or less, thereby ensuring higher resolution and less damage inflicted on surrounding tissues.

[0021] Further according to the present invention there is provided a high resolution cryosurgical method for treating a patient's prostate, comprising the step of inserting at least two cryosurgical probes of a small diameter into a prostatic tissue segment extending between the prostatic urethra and the periphery of the prostate, the probes being for producing ice-balls of sub-

stantially small diameter so as to provide a temperature of at least about  $-40^\circ\text{C}$  to a significant portion of the tissue segment while minimizing the thickness of adjacent tissues exposed to temperatures of between about  $-40^\circ\text{C}$  and about  $0^\circ\text{C}$ .

[0022] Further according to the present invention there is provided a high resolution cryosurgical method for treating a patient's organ, comprising the steps of (a) providing a guiding element including a net of apertures, each aperture being for insertion of a cryosurgical probe therethrough into the patient's organ; (b) providing a set of images of the organ by using an imaging device, such as ultrasound, MRI or CT, the images provide information on specific planes located at specific depths within the organ, each of the images includes a net of marks correlated to the net of apertures of the guiding element, wherein the marks represent the locations of ice-balls, preferably the location of their centers, which may be formed by the cryosurgical probes when introduced through the apertures of the guiding element to the distinct depths within the organ; and (c) introducing the cryosurgical probes to selected depths within the organ according to the information provided by the images and generating the ice-balls.

[0023] Further according to the present invention there is provided a high resolution cryosurgical apparatus for treating a patient's organ, comprising (a) a plurality of cryosurgical probes of small diameter, the probes being for insertion into the patient's organ, the probes further being for producing ice-balls for locally freezing selected portions of the organ; (b) a guiding element including a net of apertures for inserting the cryosurgical probes therethrough; (c) an imaging device for providing a set of images, the images being for providing information on specific planes located at specific depths within the organ, each of the images includes a net of marks correlated to the net of apertures of the guiding element, wherein the marks represent the locations of ice-balls, preferably the location of their centers, which may be formed by the cryosurgical probes when introduced through the apertures of the guiding element to the distinct depths within the organ.

[0024] Preferably, each of the cryosurgical probes includes a Joule-Thomson cooler.

[0025] Further according to the present invention there is provided a high resolution cryosurgical apparatus for treating a patient's organ, comprising (a) a plurality of cryosurgical probes of small diameter for insertion into the organ, each of the probes including a Joule-Thomson cooler, the cryosurgical probes being connectable to a manifold; (b) a manifold for distributing a high pressure gas to the cryosurgical probes, the manifold being in fluid communication with the probes and with a high pressure gas source.

[0026] Preferably, the manifold includes a cooling element for pre-cooling the high pressure gas flowing to the cryosurgical probes. The pre-cooling element may include a Joule-Thomson cooler or a cryogenic fluid. Al-

ternatively, the pre-cooling element may include an electrical cooling element or the like.

[0027] The present invention successfully addresses the shortcomings of the presently known configurations by providing cryosurgical method and device which provide high resolution of treatment along the axis of penetration of the cryosurgical probe into the patient's organ as well along the planes perpendicular to the axis of penetration.

[0028] Furthermore, the present invention successfully addresses the shortcomings of the presently known configurations by providing cryosurgical method and device which enable to effectively destroy selective portions of a patient's tissue while minimizing damage to adjacent tissues and organs.

[0029] In addition, the present invention successfully addresses the shortcomings of the presently known configurations by providing cryosurgical method and device which enable to selectively treat various portions of the tissue located at different depths of the organ, thereby effectively destroying selected portions of the tissue while avoiding the damaging of other tissues and organs located along the axis of penetration.

[0030] Furthermore, the present invention successfully addresses the shortcomings of the presently known configurations by providing cryosurgical method and device which three dimensionally map an organ of a patient so as to form a three dimensional grid thereof, and which apply a multi-probe system introduced into the organ according to the grid so as to enable high-resolution cryosurgical treatment of the organ.

[0031] The gist of the present invention is the three dimensionally controlled high resolution tissue freezing.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0032] The invention is herein described, by way of example only, with reference to the accompanying drawings, wherein:

FIG. 1a is a graph showing the profile of temperature distribution within an ice-ball formed at the tip of a cryosurgical probe;

FIG. 1b is a graph showing the effectiveness of a cryosurgical treatment, given in percentage of tissue destruction, as a function of temperature;

FIGs. 2a-2c are cross sectional views of an ice-ball formed at the tip of a conventional cryosurgical probe introduced into a patient's prostate;

FIGs. 3a-3b are cross sectional views of two ice-balls formed at the tips of cryosurgical probes according to the present invention introduced into a patient's prostate;

FIG. 4 is a cross sectional view illustrating the conventional method for treating a patient's prostate;

FIG. 5 is a cross sectional view illustrating a method according to the present invention for treating a patient's prostate;

FIG. 6a is a schematic illustration of a multi-probe cryosurgical device according to the present invention;

FIG. 6b is a schematic illustration of a pre-cooling element according to the present invention;

FIG. 7 is a schematic longitudinal section of a preferred cryosurgical probe according to the present invention;

FIG. 8 is a perspective view of a guiding element for receiving cryosurgical probes according to the present invention, the guiding element being connected to an ultrasound probe; and

FIGs. 9 and 10 illustrate a method according to the present invention including the steps of forming a three-dimensional grid of a patient's prostate and introducing cryosurgical probes thereto.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0033] The present invention is of high resolution cryosurgery method and apparatus which enable to effectively and accurately destroy a predetermined portion of a tissue while minimizing damage to adjacent healthy tissues and organs.

[0034] The principles and operation of method and apparatus according to the present invention may be better understood with reference to the drawings and the accompanying description.

[0035] Before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments or of being practiced or carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein is for the purpose of description and should not be regarded as limiting.

[0036] Referring now to the drawings, Figure 1a illustrates the profile of temperature distribution across an ice-ball formed at the tip of a cryosurgical probe. As shown, the temperature at a surface 5 of the ice-ball is 0 °C. The temperature declines exponentially towards a center 1 of the ball where it preferably reaches the value of -170 °C, such that an isothermal surface 7 of about -40 °C is typically located within the ice-ball at the half way between the center of the ball and its surface. Thus, if the ice-ball features a radius R, then the radius of the -40 °C isothermal surface 7 is about R/2.

[0037] Figure 1b is a graph showing the effectiveness of a cryosurgical treatment (given in percentage of tissue destruction) as a function of temperature. As shown, the temperature required for effectively destroying a tissue is at least about -40 °C. Accordingly, in order to effectively destroy a tissue, the isothermal surface of -40 °C (shown in Figure 1a) should be placed at the periphery of the treated tissue so that the entire area of the

treated tissue is exposed to at least about  $-40^{\circ}\text{C}$ , thereby exposing adjacent healthy tissues and organs to the external portion of the ice-ball. The application of temperatures of between about  $-40^{\circ}\text{C}$  and  $0^{\circ}\text{C}$  to such healthy tissues usually causes substantial damage thereto, which damage may result in temporary or permanent impairment of functional organs.

[0038] Figures 2a-2c illustrate prior-art cryosurgical methods wherein a single cryosurgical probe of a substantially large diameter, typically 3-5 millimeters, is introduced between the patient's prostatic urethra and the periphery of the prostate, so as to destroy the prostatic tissue extending therebetween.

[0039] Specifically, Figures 2a-2c are cross sectional views of an ice-ball 9 formed at the end of a conventional cryosurgical tip introduced into a prostate 2 of a patient. The patient's prostatic urethra, rectum and nerves are designated as 4, 3, and 6 respectively.

[0040] A single ice-ball 9 is formed within the prostatic tissue segment extending between the prostatic urethra 4 and the periphery of the prostate 13. The dimensions of a conventional cryosurgical probe are designed so as to provide an ice-ball 9 having an inner portion 10 extending through a substantially significant portion of such a tissue segment, so as to apply temperatures of between about  $-170^{\circ}\text{C}$  and about  $-40^{\circ}\text{C}$  thereto. The application of a single probe for producing a single ice-ball 9 imposes a trade-off between several options.

[0041] Figures 2a and 2b illustrate the trade-off between a first option of avoiding the damaging of the patient's prostatic urethra 4 yet damaging nerves 6 present close to the periphery 13 of the prostate 2 (Figure 2a), and a second option of avoiding the damaging of the patient's nerves 6 yet damaging urethra 4 (Figure 2b).

[0042] As shown in Figure 2a, the isothermal surface 7 of  $-40^{\circ}\text{C}$  is positioned substantially at the periphery 13 of the patient's prostate 2, such that surface 5 of the ice-ball 9 is positioned substantially near the patient's urethra 4, so as to avoid damaging of the patient's urethra 4. Thus, the inner portion 10 of ice-ball 9 effectively freezes the peripheral regions (in cross section) of the prostate, while outer portion 12 of ice-ball 9 extends through the patient's nerves 6. The application of temperatures of between about  $-40^{\circ}\text{C}$  and  $0^{\circ}\text{C}$  to the patient's nerves 6 may result in temporary or permanent impairment thereof.

[0043] Similarly, when ice-ball 9 is positioned between the patient's urethra 4 and rectum 3 in such a manner so as to avoid the damaging of urethra 4, the application of between about  $-40^{\circ}\text{C}$  and  $0^{\circ}\text{C}$  to the patient's rectum may result in temporary or permanent impairment thereof.

[0044] As shown in Figure 2b, the isothermal surface 7 of  $-40^{\circ}\text{C}$  is positioned substantially near the patient's urethra 4 such that surface 5 of ice-ball 9 is positioned substantially near the patient's nerves 6 and/or rectum 3 (not shown), so as to avoid damaging of the patient's nerves 6 and/or rectum 3. Thus, inner portion 10 of ice-

ball 9 effectively freezes the central regions (in cross section) of prostate 2, while outer portion 12 of ice-ball 9 extends through the patient's urethra 4. The application of temperatures of between about  $-40^{\circ}\text{C}$  and  $0^{\circ}\text{C}$  to the patient's urethra 4 may result in temporary or permanent impairment thereof.

[0045] However, none of the alternatives shown in Figures 2a and 2b provides an effective treatment (temperature of at least about  $-40^{\circ}\text{C}$ ) to the entire prostatic tissue segment extending between urethra 4 and the periphery 13 of the prostate, thereby exposing the patient to the risk of malignancy.

[0046] Figure 2c shows another possible alternative wherein a thicker cryosurgical probe, having a tip diameter of between 4 and 6 millimeters is used for producing a larger ice-ball, of about 4-5 centimeters in diameter, so as to enable effective treatment of the entire prostatic tissue segment extending between the urethra 4 and periphery 13 of prostate 2. As shown, inner portion 10 of the ice-ball 9 extends through the entire tissue segment (in cross section) between urethra 4 and periphery 13 of the prostate, thereby exposing urethra 4 and nerves (not shown), as well as the rectum 3, to outer portion 12 of the ice-ball 9.

[0047] The thickness (in cross section) of tissues exposed to outer portion 12 of the ice-ball is about  $R/2$ , wherein  $R$  is the radius of ice-ball 9. Thus, the volume of adjacent tissues exposed to damage becomes substantially greater than the volume of the treated tissue.

[0048] Thus, the conventional cryosurgical probes and methods fail to provide the necessary resolution of treatment required for enabling an accurate and effective destruction of a tissue while preserving other tissues and organs adjacent thereto.

[0049] Figures 3a and 3b are schematic illustrations of a cryosurgical method according to the present invention, wherein a plurality of cryosurgical probes of substantially small diameters are introduced between the patient's prostatic urethra 4 and periphery 13 of prostate 2, so as to destroy the prostatic tissue extending therebetween.

[0050] As shown in Figure 3a, preferably two probes are introduced into a prostatic tissue segment extending between the patient's prostatic urethra 4 and periphery 13 of prostate 2, so as to form two smaller ice-balls, 9a and 9b.

[0051] According to the configuration shown in Figure 3a, each of ice-balls 9a and 9b features a radius of  $R/2$ , which is half the radius of ice-ball 9 shown in Figure 2c. Accordingly, ice-balls 9a and 9b include respective inner portions, 14a and 14b, each having a radius of  $R/4$ , and respective outer portions, 16a and 16b, each having a thickness of  $R/4$ .

[0052] Therefore, by introducing two probes of a small diameters rather than a single probe of a larger diameter into the tissue segment extending between prostatic urethra 4 and periphery 13 of prostate 2, the thickness of adjacent tissues exposed to damage is substantially

decreased. The specific example of Figure 3a shows that the thickness (in cross section) of adjacent tissues exposed to between about -40 °C and 0 °C is only  $R/4$ , which is half the thickness and respectively much less the volume (e.g., 8 fold less), exposed to damage when using the prior art method (shown in Figure 2c).

[0053] By further decreasing the diameter of the cryosurgical probes and introducing a plurality of probes into the tissue segment extending between urethra 4 and periphery 13 of prostate 2, the damage to surrounding tissues may be further minimized, thereby improving the resolution of the cryosurgical treatment.

[0054] Another embodiment is shown in Figure 3b, wherein two probes are introduced into the tissue segment extending between the patient's urethra 4 and periphery 13 of prostate 2, so as to form two ice-balls 9a and 9b, such that inner portion 14a of ice-ball 9a is substantially spaced from inner portion 14b of ice-ball 9b, and outer portion 16a of ice-ball 9a partially overlaps outer portion 16b of ice-ball 9b, the overlapping region being designated as 17. The specific example shown in Figure 3b is of two ice-balls each having a radius of  $R/5$ , wherein R is the radius of a conventional ice-ball as shown in Figure 2c. By using such configuration, the thickness of adjacent tissues exposed to damage is decreased to  $R/5$  and the volume thereof is decreased respectively. It will be appreciated that in the example given substantial fractions of region 17, from which heat is extracted by two probes, will become cooler than -40 °C.

[0055] The specific examples shown in Figures 3a and 3b are of two ice-balls having tangent and spaced inner portions, respectively. However, a plurality of probes may be used, each having a distinct diameter, the inner portions of which being tangent or spaced.

[0056] Referring to Figure 4, a prior-art cryosurgical method is shown, illustrating the distribution of a plurality of cryosurgical probes across a patient's prostate, wherein a single probe is introduced into a tissue segment extending between prostatic urethra 4 and periphery 13 of prostate 2. According to such a prior art method, about 5-7 probes are introduced into the patient's prostate, wherein each of the probes features a diameter of about 3 millimeters. Figure 4 shows a specific example wherein five probes are introduced so as to form five ice-balls having inner portions 10a-10e and outer portions 12a-12e. As shown, an effective treatment is provided by inner portions 10a-10e, and regions therebetween marked 19, only to limited regions of the prostate, wherein the damage caused to adjacent tissues such as the patient's urethra 4, rectum 3 and nerve 6b by outer portions 12a-12e is considerable.

[0057] Figure 5 shows a preferred distribution of cryosurgical probes according to a method of the present invention. As shown, at least two cryosurgical probes of substantially small diameter are introduced into specific segments of prostatic tissue extending between urethra 4 and periphery 13 of prostate 2. Figure 5 shows a specific example wherein twenty probes are introduced into

the patient's prostate 2, including five pairs of inner and outer cryosurgical probes located at specific segments of the prostate extending from the urethra 4 to periphery 13, and additional (five pairs in the example given) of outer cryosurgical probes are introduced therebetween. The inner portions of the ice-balls formed by the pairs of outer and inner probes are designated as 14a and 14b, respectively, wherein the inner portions of the ice-balls formed therebetween are designated as 14c.

[0058] The diameter of a single cryosurgical probe according to the present invention is preferably between about 1.2 millimeters and about 1.4 millimeters.

[0059] As shown, such distribution of substantially small diameter cryosurgical probes enables to provide an effective treatment of at least -40 °C to a larger area of the prostatic tissue while substantially minimizing the thickness of healthy adjacent tissues exposed to damage.

[0060] Thus, a method according to the present invention substantially increases the effectiveness and resolution of treatment relative to the prior art method.

[0061] The pattern of distribution of probes shown in Figure 5 includes an inner circle and an outer circle of probes, wherein a portion of the probes is arranged in pairs of an inner probe and an outer probe. According to another configuration (not shown), the probes are arranged in an inner circle and an outer circle, but not necessarily in pairs of an inner probe and an outer probe.

[0062] The probes may be sequentially introduced to and extracted from the patient's prostate so as to sequentially freeze selected portions thereof. A method of quick extraction of the probes without tearing pieces of tissue from the patient, which stick to the tip of the probe, is disclosed hereinunder.

[0063] The introduction of a plurality of small diameter cryosurgical probes improves the resolution of treatment along the planes perpendicular to the axis of penetration of the probes into the prostate. However, the prostate, as other anatomical organs, features an asymmetric three dimensional shape. Thus, a specific pattern of distribution of probes may provide an effective treatment to a distinct plane located at a specific depth of penetration, but at the same time may severely damage non-prostatic tissues located at other depths of penetration. The prior art fails to provide cryosurgical method and apparatus which enable high resolution of treatment along and perpendicular to the axis of penetration of the probes into a patient's organ.

[0064] According to the present invention there are provided cryosurgical method and apparatus which enable high resolution of treatment along the axis of penetration of the cryosurgical probe into the patient's organ as well as along the planes perpendicular to the axis of penetration, wherein these high resolutions are achieved by forming a three-dimensional grid of the organ, preferably by using ultrasound imaging, and inserting each of the cryosurgical probes to a specific depth within the organ according to the information provided

by the grid.

[0065] Referring to Figures 6a, 6b and 7, a cryosurgical apparatus according to the present invention includes a plurality of cryosurgical probes 53, each having an operating tip 52 including a Joule-Thomson cooler for freezing a patient's tissue and a holding member 50 for holding by a surgeon. As shown in Figure 7, operating tip 52 includes at least one passageway 78 extending therethrough for providing gas of high pressure to orifice 80 located at the end of operating tip 52, orifice 80 being for passage of high pressure gas therethrough, so as to cool operating tip 52 and produce an ice-ball at its end 90. Gases which may be used for cooling include, but are not limited to argon, nitrogen, air, krypton, CO<sub>2</sub>, CF<sub>4</sub>, xenon, or N<sub>2</sub>O.

[0066] When a high pressure gas such as argon expands through orifice 80 it liquefies, so as to form a cryogenic pool within chamber 82 of operating tip 52, which cryogenic pool effectively cools surface 84 of operating tip 52. Surface 84 of operating tip 52 is preferably made of a heat conducting material such as metal so as to enable the formation of an ice-ball at end 90 thereof.

[0067] Alternatively, a high pressure gas such as helium may be used for heating operating tip 52 via a reverse Joule-Thomson process, so as to enable treatment by cycles of cooling-heating, and further for preventing sticking of the probe to the tissue when extracted from the patient's body, and to enable fast extraction when so desired.

[0068] When a high pressure gas such as helium expands through orifice 80 it heats chamber 82, thereby heating surface 84 of operating tip 52.

[0069] Operating tip 52 includes at least one evacuating passageway 96 extending therethrough for evacuating gas from operating tip 52 to the atmosphere.

[0070] As shown Figure 7, holding member 72 may include a heat exchanger for pre-cooling the gas flowing through passageway 78. Specifically, the upper portion of passageway 78 may be in the form of a spiral tube 76 wrapped around evacuating passageway 96, the spiral tube being accommodated within a chamber 98. Thus, gas evacuated through passageway 96 may pre-cool the incoming gas flowing through spiral tube 76.

[0071] As further shown in Figure 7, holding member 72 may include an insulating body 92 for thermally insulating the heat exchanger from the external environment.

[0072] Furthermore, operating tip 52 may include at least one thermal sensor 87 for sensing the temperature within chamber 82, the wire 89 of which extending through evacuating passageway 96 or a dedicated passageway (not shown).

[0073] In addition, holding member 72 may include a plurality of switches 99 for manually controlling the operation of probe 53 by a surgeon. Such switches may provide functions such as on/off, heating, cooling, and predetermined cycles of heating and cooling by selectively and controllably communicating incoming pas-

sageway 70 with an appropriate external gas container including a cooling or a heating gas.

[0074] As shown in Figure 6a, each of cryosurgical probes 53 is connected via a flexible connecting line 54 to a connecting site 56 on a housing element 58, preferably by means of a linking element 51. Cryosurgical probes 53 may be detachably connected to connecting sites 56.

[0075] Preferably, evacuating passageway 96 extends through connecting line 54, such that the outgoing gas is evacuated through an opening located at linking element 51 or at any other suitable location, e.g., manifold 55, see below. Preferably, line 54 further includes electrical wires for providing electrical signals to the thermal sensor and switches (not shown).

[0076] Each of cryosurgical probes 53 is in fluid communication with a manifold 55 received within a housing 58, manifold 55 being for distributing the incoming high pressure gas via lines 57 to cryosurgical probes 53.

[0077] As shown, housing 58 is connected to a connector 62 via a flexible cable 60 including a gas tube (not shown), connector 62 being for connecting the apparatus to a high pressure gas source and an electrical source.

[0078] The apparatus further includes electrical wires (not shown) extending through cable 60 and housing 58 for providing electrical communication between the electrical source and cryosurgical probes 53.

[0079] Preferably, housing 58 includes a pre-cooling element, generally designated as 61, for pre-cooling the high pressure gas flowing to cryosurgical probes 53. Preferably, pre-cooling element 61 is a Joule-Thomson cooler, including a tubular member 48 received within a chamber 49, tubular member 48 including an orifice 59 for passage of high pressure gas therethrough, so as to cool chamber 49, thereby cooling the gas flowing through tubular member 48 into manifold 55.

[0080] Another configuration of a pre-cooling element 61 is shown in Figure 6b, wherein tubular member 48 is in the form of a spiral tube wrapped around a cylindrical element 47, so as to increase the area of contact between tubular member 48 and the cooling gas in chamber 49.

[0081] According to yet another configuration (not shown), housing 58 includes a first tubular member for supplying a first high pressure gas to manifold 55, and a second tubular member for supplying a second high pressure gas to pre-cooling element 61. Any combination of gases may be used for cooling and/or heating the gases flowing through such tubular members.

[0082] Alternatively, a cryogenic fluid such as liquid nitrogen may be used for pre-cooling the gas flowing through housing 58. Alternatively, an electrical pre-cooling element may be used for pre-cooling the gas.

[0083] Preferably, thermal sensors (not shown) may be located within cable 60 and manifold 55 for measuring the temperature of gas flowing therethrough.

[0084] Referring to Figures 8-10, method and appa-

ratus according to the present invention applies an imaging device such as ultrasound, MRI or CT, so as to form a three-dimensional grid of the patient's treated organ, e.g., prostate, the three dimensional grid serves for providing information on the three dimensional shape of the organ. Each of the cryosurgical probes is then inserted to a specific depth within the organ according to the information provided by the grid.

[0085] As shown in Figure 8, an ultrasound probe 130 is provided for insertion into the patient's rectum, ultrasound probe 130 being received within a housing element 128. A guiding element 115 is connected to housing element 128 by means of a connecting arm 126. As shown, guiding element 115 is in the form of a plate 110 having a net of apertures 120, each aperture serves for insertion of a cryosurgical probe therethrough. Preferably, the distance between each pair of adjacent apertures 120 is between about 2 millimeters and about 5 millimeters.

[0086] As shown in Figure 9, ultrasound probe 130 is introduced to a specific depth 113 within the patient's rectum 3. A net of marks 112 is provided on the obtained ultrasound image 114, the net of marks 112 on image 114 being accurately correlated to the net of apertures 120 on guiding element 115.

[0087] Thus, marks 112 on image 114 sign the exact locations of the centers of ice-balls which may be formed at the end of the cryosurgical probes inserted through apertures 120 to the patient's prostate 2, wherein image 114 relates to a specific depth of penetration 113 of the cryosurgical probes into the prostate 2.

[0088] As shown in Figure 9, ultrasound probe 130 is gradually introduced to various depths 113 of rectum 3, thereby producing a set of images 114, wherein each image relates to a respective depth of penetration into the prostate 2. Thus, each of images 114 relates to a specific plane perpendicular to the axis of penetration of the cryosurgical probes.

[0089] The set of images 114 provides a three dimensional grid of the prostate. Such three-dimensional grid is then used for planning the cryosurgical procedure.

[0090] For example, the introduction of a cryosurgical probe along a given axis of penetration to a first depth may effectively destroy a prostatic tissue segment, while introduction of the probe to a second depth may severely damage the prostatic urethra.

[0091] Since the ice-ball is locally formed at the end of the cryosurgical probe, each probe may be introduced to a specific depth so as to locally provide an effective treatment to a limited portion of the prostate while avoiding the damaging of non-prostatic or prostatic tissues located at other depths of penetration.

[0092] Figure 10 shows the insertion of an operating tip 52 of a cryosurgical probe 50 through an aperture of guiding element 115 into the prostate 2 of a patient.

[0093] Preferably, a plurality of cryosurgical probes are sequentially inserted through apertures 120 of guiding element 115 into the patient's prostate, wherein each

probe is introduced to a specific depth, thereby providing substantially local effective treatment to distinct segments of the prostatic tissue while avoiding the damaging of other prostatic or non-prostatic tissue segments.

[0094] Preferably, each of the cryosurgical probes includes a scale for indicating the depth of penetration into the prostate.

[0095] Although the invention has been described in conjunction with specific embodiments thereof, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art. Accordingly, it is intended to embrace all such alternatives, modifications and variations that fall within the spirit and broad scope of the appended claims.

## Claims

1. A high resolution cryosurgical apparatus for treating a patient's organ, comprising the steps of:
  - (a) a plurality of cryosurgical probes of small diameter, said probes being for insertion into the patient's organ, said probes being for producing ice-balls for locally freezing selected portions of the organ;
  - (b) a guiding element including a net of apertures for inserting said cryosurgical probes therethrough; and
  - (c) an imaging device for providing a set of images, said images being for providing information on specific planes located at specific depths within the organ, each of said images including a net of marks correlated to said net of apertures of said guiding element, wherein said marks representing the locations of ice-balls which may be formed by said cryosurgical probes when introduced through said apertures of said guiding element to said distinct depths within the organ, thereby enabling to select an appropriate depth of penetration to each of said cryosurgical probes.
2. The apparatus of claim 1, wherein said imaging device is selected from the group consisting of a CT device, an MRI device and an ultrasound probe.
3. The apparatus of claim 1, wherein said cryosurgical probes feature a diameter of between about 0.2 millimeters and about 1.4 millimeters.
4. The apparatus of claim 1, wherein each of said cryosurgical probes includes a Joule-Thomson cooler.
5. The apparatus of claim 1, wherein said probes are connected to a manifold, said manifold serves for distributing a high pressure gas to said probes.



6. The apparatus of claim 5, wherein said manifold includes a cooling element for pre-cooling said high pressure gas flowing to said cryosurgical probes.
7. The apparatus of claim 6, wherein said pre-cooling element includes a Joule-Thomson cooler. 5
8. A high resolution cryosurgical apparatus for treating a patient's organ, comprising: 10
  - (a) a plurality of cryosurgical probes of small diameter for insertion into the organ, each of said probes including a Joule-Thomson cooler, said cryosurgical probes being connectable to a manifold; and 15
  - (b) a manifold for distributing a high pressure gas to said cryosurgical probes, said manifold being in fluid communication with said probes and with a high pressure gas source. 20
9. The apparatus of claim 8, wherein said cryosurgical probes are detachably connected to said manifold.
10. The apparatus of claim 8, wherein said manifold includes a cooling element for pre-cooling said high pressure gas flowing to said cryosurgical probes. 25
11. The apparatus of claim 8, wherein said pre-cooling element includes a Joule-Thomson cooler. 30
12. The apparatus of claim 8, wherein a first high pressure gas is provided to said Joule-Thomson cooler of said manifold and a second high pressure gas is provided to said Joule-Thomson coolers of said cryosurgical probes. 35
13. The apparatus of claim 8, wherein said pre-cooling element includes an electrical cooling element.
14. The apparatus of claim 8, wherein said pre-cooling element includes a cryogenic fluid. 40
15. The apparatus of claim 8, wherein said cryosurgical probes feature a diameter of between about 0.2 millimeters and about 1.4 millimeters. 45
16. The apparatus of claim 8, wherein each of said cryosurgical probes includes a thermal sensor.
17. The apparatus of claim 8, wherein each of said cryosurgical probes includes a heat exchanger. 50
18. The apparatus of claim 8, wherein each of said cryosurgical probes includes switches for manually controlling the operation of said probes. 55

FIG. 1a




FIG. 1b




FIG. 2a





FIG. 2b



F16. 2C




FIG. 3a




FIG. 3b




FIG. 4




FIG. 5




FIG. 6a




FIG. 6b






FIG. 7




FIG. 8




FIG. 9





FIG. 10



European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 99 20 0974

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.8)
X	US 5 603 221 A (MAYTAL BEN-ZION) 18 February 1997	8,9, 16-18	A61B17/36
Y	* column 6, line 25 - line 37; figure 2 *	10-15	
X	WO 96 37158 A (CHINN DOUGLAS O) 28 November 1996	8,17	
Y	* page 8, line 11 - line 17; figure 1 * * page 19, line 6 - line 13; figure 9 *	1,2,4,5	
Y	US 5 678 549 A (HEYWANG-KOEBRUNNER SYLVIA ET AL) 21 October 1997	1,2,4,5	
	* column 5, line 16 - line 19; figures 2,3 *		
Y	US 4 829 785 A (HERSEY DEVIN W) 16 May 1989	10-12	
A	* abstract *	6,7	
Y	WO 98 06339 A (ROWLAND STEPHEN JAMES) 19 February 1998	13,14	
A	* page 4, line 17 - line 21; figure 1 *	6	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
Y	US 5 108 390 A (POTOCKY CLIFFORD E ET AL) 28 April 1992	15	A61B
A	* column 3, line 9 - line 13; figure 2 *	3	
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>1 July 1999</b>	Examiner <b>Mayer, E</b>
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 (03/82) (P4/C01)

EP 0 947 172 A1

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 20 0974

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

01-07-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5603221 A	18-02-1997	NONE	
WO 9637158 A	28-11-1996	CA 2222045 A US 5647868 A AU 2763495 A EP 0833590 A	28-11-1996 15-07-1997 11-12-1996 08-04-1998
US 5678549 A	21-10-1997	DE 4225001 C DE 4325206 A JP 6181908 A	18-11-1993 03-02-1994 05-07-1994
US 4829785 A	16-05-1989	US 4990412 A	05-02-1991
WO 9806339 A	19-02-1998	AU 3948197 A GB 2331847 A	06-03-1998 02-06-1999
US 5108390 A	28-04-1992	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.